Product data sheet

Power tools for trade & industry

Straight Grinder

GGS 30 LS



Powerful, convenient, protective: the high-performance die grinder for versatile grinding tasks

The most important data

Rated input power	650 W
No-load speed	7,000 – 33,000 rpm

Part Number 0 601 2B5 060

Technical data

Technical data

No-load speed	7,000 – 33,000 rpm
Rated input power	650 W
Power output	400 W
Spindle collar diameter	43 mm
Weight	1.7 kg
Max. collet diameter	6 mm, 1/4", 3 mm, 8 mm
Max. grinding tool diameter	25 mm
Spanner size of locking nut	17 mm
Spanner size of grinding spindle	15 mm
Max. polishing tool diameter	50 mm
Switch	Lockable Switch
Packaging dimensions (width x length x height)	135 x 495 x 135 mm
Voltage, electrical	110 V
Collet diameter supplied	6 mm

Noise/vibration information

Surface grinding (roughing with grinding tool diameter of 25 mm)

Vibration emission value ah	6 m/s²
Uncertainty K	1.5 m/s²

Surface grinding (roughing with grinding tool diameter of 50 mm)

Vibration emission value ah	21 m/s²
Uncertainty K	1.5 m/s²

Advantages:

- Easy and convenient accessory change with handy spindle lock function
- Ergonomic tool with a powerful 750-watt grinding performance
- All-round safety features with KickBack Control, soft start, and restart protection
- Versatile application thanks to speed selection and long, slim grinding spindle
- Ideal for heavy-duty metal work and stone carving, even in tight spaces

