Rotary Hammer

HR4013C

1 100 W • SDS-MAX • 40 mm • 8.0 J

Efficient dual-action hammer with integrated anti-vibration technology

An efficient 1 100 W combi hammer with a unique AVT anti-vibration system for SDS-MAX blades. Masonry drilling capacity of 40 mm and impact energy of 8.0 J. With its drilling and chipping functions, this tool is an ideal choice for renovation and building work.



AVT ANTI VIBRATION TECHNOLOGY SOFT NO LOAD

Technical specifications

Continuous Input Power	1100 W
No load speed	250 - 500 min^{-1}
Impacts per Minute (IPM)	1450 - 2900 min^{-1}
Max. Drilling Diameter in Concrete	40 mm
Optimum Drilling Diameter Range in Concrete	16 - 35 mm
Impact Energy	8,0 J
Drilling diameter with TCT core bit	105 mm
Power Supply Cord	5,0 m
Sound Power Level (L_{WA})	104 dB(A)
Sound Pressure Level (L_{pA})	93 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Chiselling	4,8 m/s^2
Weight Without Cable	6,8 kg
Product Dimensions (L x W x H):	479 x 112 x 263 mm

User benefits

- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- Vibration dampened handle design for tireless work
- The service light indicates the need for carbon brush replacement and malfunctions in the switch and connection cable
- Impact drilling and spike function
- Standard electronics: power boost under load
- Vibration absorbing housing helps to reduce vibration
- Variable speed control dial enables user to match the speed to the application for greater versatility
- Lock-on feature for continuous operation

EAN 0088381651332

Link to product - www.makitauk.com

Related products

Optional AC

123138-5
Straight Side Handle



194683-7
Grease vessel set, 100 ml



198993-4
Grease vessel for bit 100 ml



199144-2
Dust Extraction Attachment



321248-4
Depth Gauge

331955-1
Depth Gauge

Other

User manual

Parts drawing