Die Grinder

GD0600

400 W • 25 000 min^{-1} • 6 mm

Compact tool with safety switch underneath

A slimline, light die grinder with a 6 mm collet and paddle switch. Suitable for small-scale grinding, including burr removal. Achieves a high speed: 25 000 min-1.



Technical specifications

Continuous Input Power	400 W
No load speed	25000 min^{-1}
Collet Capacity	6 mm
Wheel point max.	38 mm
Collar Clamping Diameter	35/43 mm
Power Supply Cord	2,5 m
Sound Pressure Level (L_{pA})	74 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Weight Without Cable	1,6 kg
Product Dimensions (L x W x H):	358 x 82 x 82 mm
Vibration Level, Surface Grinding	3,5 m/s^2
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s^2

User benefits

- Slim body design for a good grip
- Large paddle switch for easy operation right or left handed
- Vent slots designed to direct exhaust air away from the user

EAN 0088381073318

Link to product - www.makitauk.com

Related products

Optional AC

763620-8
Collet cone 6 mm



763627-4
Collet cone 3 mm



763664-8
Collet nut 6 mm



781039-9
Wrench 13

781203-2
Wrench 13

781206-6
Wrench 19

B-36865
Flap wheel Ø50mm



B-36871
Flap wheel Ø50mm



B-36887
Flap wheel Ø50mm



B-36902
Flap wheel Ø50mm



B-52716
TCT Burr 10 x 20 x 6 mm, Standard

B-52722
TCT Burr 10 x 20 x 6 mm, Diamond

B-52738
TCT Burr 10 x 20 x 6 mm, Non-

B-52744
TCT Burr 10 x 20 x 6 mm, Standard

B-52750
TCT Burr 10 x 20 x 6 mm, Diamond

B-52766
TCT Burr 10 x 20 x 6 mm, Non-

B-52772
TCT Burr 10 x 20 x 6 mm, Standard

B-52788
TCT Burr 10 x 20 x 6 mm, Diamond

B-52794
TCT Burr 10 x 20 x 6 mm, Non-

B-52803
TCT Burr 10 x 25 x 6 mm, Standard

B-52819
TCT Burr 10 x 25 x 6 mm, Diamond

B-52825
TCT Burr 10 x 25 x 6 mm, Non-

B-52831
TCT Burr 10 x 20 x 6 mm, Standard

B-52847
TCT Burr 10 x 20 x 6 mm, Diamond

B-52853
TCT Burr 10 x 20 x 6 mm, Non-

Other

User manual

Parts drawing