Impact Drill

HP1640K

680 W • 16 mm • 0 – 2 800 min^{-1}

Compact drill with hammer and drive functions

Compact 680 W percussion drill with a masonry drilling capacity of 16 mm. A slimline frame and large switch for added usability. With rugged aluminium housing for gear drive. 13 mm quick action drill chuck. Comes in a case.



TECHNICAL SPECIFICATIONS

Maximum Output Power	680 W
No load speed	0 - 2800 min^{-1}
Impact	0 - 44 800 min^{-1}
Max. Drilling Diameter in Wood	30 mm
Max. Drilling Diameter in Concrete	16 mm
Max. Drilling Diameter in Steel	13 mm
Drill Chuck Capacity	1,5 - 13 mm
Collar Clamping Diameter	43 mm
Power Supply Cord	2,0 m
Plastic Carrying Case	✓
Side Grip	✓
Sound Power Level (L_{WA})	103 dB(A)
Sound Pressure Level (L_{pA})	92 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s^2

USER BENEFITS

- Drill with drilling and impact drilling
- Rubberized soft grip for more comfort and control
- Same speed and torque in both directions with reverse gear.
- Variable speed control dial enables user to match the speed to the application
- Double insulated

Link to Product page - www.makita.ae

RELATED PRODUCTS

STANDARD ACCESSORIES

324219-0
DEPTH GAUGE

763448-4
Chuck key S13, 13 mm



OPTIONAL ACCESSORIES

324219-0
DEPTH GAUGE

763448-4
Chuck key S13, 13 mm



OTHER

User manual