# Rotary Hammer

# HR2630

## 800 W • SDS-PLUS • 26 mm • 2.4 J

**Professional three-mode rotary hammer**

Efficient rotary hammer compatible with SDS-PLUS bits. Suitable for impact and unstressed drilling, plus chipping. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min-1 from a switch. Impact energy of 2.4 J and optimal drilling range of 8 – 18 mm in concrete. Max. drilling capacity of 26 mm in concrete.

## Technical specifications

| | |
|---|---|
| Continuous Input Power | 800 W |
| No load speed | 0 - 1200 $min^{-1}$ |
| Impacts per Minute (IPM) | 0 - 4600 $min^{-1}$ |
| Max. Drilling Diameter in Wood | 32 mm |
| Max. Drilling Diameter in Concrete | 26 mm |
| Max. Drilling Diameter in Steel | 13 mm |
| Optimum Drilling Diameter Range in Concrete | 4 - 18 mm |
| Impact Energy | 2,4 J |
| Power Supply Cord | 2,5 m |
| Drilling diameter with TCT core bit | 68 mm |
| Adapted for SDS-PLUS bits | ✓ |
| Sound Power Level ($L_{WA}$) | 101 dB(A) |
| Sound Pressure Level ($L_{pA}$) | 93 dB(A) |
| Noise Uncertainty (K Factor) | 3 dB(A) |

## User benefits

- Same speed and torque in both directions with reverse gear
- The rubber coating on the handle ensures a firm working grip
- Torque limiter stops rotation if bit jams for increased operator safety and enhanced motor protection
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- Depth gauge for increased drilling consistency
- Variable speed control dial enables user to match the speed to the application for greater versatility

## EAN 0088381687300

**Link to product - www.makitauk.com**

# Related products

## Optional AC

**193472-7**
Dust extraction set Ø 25 / 31 mm

**821550-0**
Makpac case (2)

**824914-7**
Plastic Carrying Case

**331886-4**
Depth Gauge

**821775-6**
Carrying Case

**837651-4**
MakPac (2) Inlay

## Other

**User manual**

**Parts drawing**